SLIDE, FILM & OPTICAL PROJECTION LAMPS

- Double Contact Bayonet Base - BA15d
  Single Contact Bayonet Base BA15s
- Operate Base Down (except as noted)

Watts (W)	Ordering Code	Lamp Description	Volts (V)	Dimensions (mm) Dia (A)	MOL (B)	LCL (C)	Filament Type	Lumens (lm)	Color Temp (K)	Avg Life (h)	Burn Position	Case Qty	Fig No
		Double Contact Bayonet Base – BA15d											
30	1000060	BLC	120	35	60.3	34.9	CC-2V	400	2775	50	BD/Hor	12	1
50	1000062	BLX	120	35	60.3	34.9	CC-2V	780	2850	50	BD/Hor	12	1
75	1000066	BNF	120	35	60.3	34.9	CC-2V	1300	2900	50	BD/Hor	12	1
75	1000128	CBX/CBS	120	25	79.4	34.9	CC-13	1250	2950	50	BD	25	3
100	1000132	CEA/CEB/CDK	120	25	78.0	35.0	CC-13	1800	2970	50	BD	25	3
200	1000051	BEJ	120	38	66.7	34.9	CC-2V	4600	3100	25	BD	12	2
		Single Contact Bayonet Base – BA15s											
75	1000100	BXE	10	25	75.0	44.5	C-8	1700	—	100	BD	12	3
100	1000065	BMY	120	35	60.3	34.9	CC-13	1860	2950	50	BD/Hor	25	1
150	1000136	CHK	120	25	92.1	34.9	CC-13	2995	2850	500	BD	25	4



Fig.1 Fig.2 Fig.3 Fig.4

• Mogul Screw Base - E39

Watts (W)	Ordering Code	Lamp Description	Volts (V)	Dimensions (mm) Dia (A)	MOL (B)	LCL (C)	Filament Type	Lumens (lm)	Color Temp (K)	Avg Life (h)	Burn Position	Case Qty	Fig No
		Mogul Screw Base – E39											
1000	1000219	DRW	120	64.0	230	125.0	C-13D	27400	3250	25	BD	25	1



Fig.1

- 4-Pin Base - G17t-7
- 1 9/16" (39.7mm) Light Center Length
- Proximity & Opaque Reflector Lamps

Watts (W)	Ordering Code	Lamp Description	Volts (V)	Dimensions (mm) Dia (A)	MOL (B)	LCL (C)	Filament Type	Color Temp (K)	Avg Life (h)	Burn Position	Case Qty	Fig No
		4-Pin Base – G17t-7 - 1 9/16" (39.7mm) LCL										
500	1000047	BCK	120	19.5	88.9	38.7	C-13D	❍3250	50	BD/Hor	12	1

❍ Proximity Reflector



Fig.1

FILM & OVERHEAD PROJECTION LAMPS

- Medium Prefocus Base - P28s
- 2 3/16" (55.5mm) & 3 1/2" (88.9mm) Light Center Length
- Medium Screw Base - E26
- 3" (76mm) Light Center Length

Watts (W)	Ordering Code	Lamp Description	Volts (V)	Dimensions (mm) Dia (A)	MOL (B)	LCL (C)	Filament Type	Lumens (lm)	Color Temp (K)	Avg Life (h)	Burn Position	Case Qty	Fig No
		Medium Prefocus Base – P28s - 2 3/16" (55.5mm) LCL											
500	1000179	DEB	120	38.0	144	88.9	C-13D	9000	2850	800	BU	25	1
500	1000205	DMX	120	64.0	144	55.5	C-13	13200	3200	50	BD	25	2
500	1000211	DNW	120	64.0	145	55.5	C-13	10000	3050	500	BD/Hor	25	2
		Medium Screw Base – E26 - 3" (76mm) LCL											
750	1000169	DCX	120	38.0	139.7	76.2	C-13D	19500	3200	25	BD	25	3



Fig.1 Fig.2 Fig.3

INCANDESCENT PROJECTION LAMPS

- Projection Sound Lamps
- Single Contact Prefocus Base - P30s
  Mogul Prefocus Base - P40s

Watts (W)	Ordering Code	Lamp Description	Volts (V)	Amps (A)	Dimensions Dia (mm)	Dimensions MOL (mm)	Dimensions LCL (mm)	Filament Type	Lumens (lm)	Color Temp (K)	Avg Life (h)	Burn Position	Case Qty
		Mogul Prefocus Base – P40s											
1500	1000221	DTJ	120	——	64	242	87.3	C-13D	42500	3200	25	BD	25



- Medium Screw Base - E26

Watts (W)	Ordering Code	Lamp Description	Volts (V)	Dimensions (mm) Dia (A)	Dimensions (mm) MOL (B)	Lumens (lm)	Color Temp (K)	Avg Life (h)	Burn Position	Case Qty	Fig No
		Medium Screw Base – E26									
75	1001266	PH140, S-14	120	44.0	86.0	1150	2900	50	Univ	30	1
75	1001267	PH211, A-21	115-125	67.0	126.0	1000	3000	100	Univ	30	2
150	1001268	PH212, A-21	115-125	67.0	126.0	2300	3050	100	Univ	30	2
250	1001269	PH213, A-21 NO.1	115-125	67.0	126.0	7000	3400	3	Univ	30	2



Fig.1



Fig.2

INCANDESCENT PHOTOFLOOD LAMPS

- Medium Screw Base - E26
- Inside Frosted & Blue Bulbs
- 115-120 Volts

Watts (W)	Ordering Code	Lamp Description	Volts (V)	Dimensions (mm) Dia (A)	Dimensions (mm) MOL (B)	Approx Lumens (lm)	Color Temp (K)	Avg Life (h)	Burn Position	Application	Case Qty	Fig No
		Medium Screw Base – E26										
250	1000026	BBA, A-21 NO.1	120	67.0	126.0	8500	3400	3	Univ	Photoflood	30	1
250	1000046	BCA, A-21 NO. B1 BLUE	120	67.0	126.0	2970	5760	3	Univ	Photoflood	30	1
250	1000265	ECA, A-23	120	75.0	140.0	6500	3200	20	Univ	Photoflood	30	1
300	1000024	BAH, INC115V-300W	115	66.7	125.4	9300	3200	20	Univ	Photocopy	30	1
500	1000263	EBV, PS-25 NO.2	120	80.0	152.0	17000	3400	6	Univ	Photoflood	30	2
500	1000264	EBW, PS-25 NO. B2/BLUE	120	80.0	152.0	6680	4840	6	Univ	Photoflood	30	2
500	1000266	ECT, PS-25 3200K	120	79.4	152.0	13650	3200	60	Univ	Photoflood	30	2



Fig.1



Fig.2

Watts (W)	Ordering Code	Lamp Description	Volts (V)	System Cross Reference	Case Qty
		Entertainment Flash			
1000	5000916	UA-AF1, 1000W, 400V	400	Dataflash HO1	6
1000	5000177	UA-DF1, 1000W, 400V	400	Dataflash SO1	6