



Utopia™ LED S14

LED S14 Lamps for Use in Marquees, Signs and Amusement Applications

Utopia™ LED S14 series of lamps are not only built to operate in the demanding conditions of signs, marquees and amusement rides, but they are also uniquely designed to provide an appearance that replicates traditional incandescent lamps. Utopia lamps do all of this while saving up to 80% in energy costs.

The Utopia LED S14 lamps use special AC LEDs which allow them to operate with fewer electrical components. This reduces the number of potential points of failure, providing you with a more reliable product. This higher level of reliability is especially important in hard to change applications. These dimmable LED lamps consume only 2 watts of power and are able to be cycled and flashed. Their life is rated for up to 50,000 hours, and they're approved for wet location operation.

USHIO is proud to stand behind these energy-saving LED lamps with a 5-year warranty. The Utopia LED S14 lamps come in E26 medium base and are available in red, green, blue, and yellow.




FEATURES & BENEFITS

- Energy Saving
- Dimmable
- Able to Cycle & Flash
- Unique Optic for a Dramatic Appearance
- AC LED – Less Components Mean More Reliability
- Wet Location Rated for Indoor or Outdoor Use
- Direct Replacement for 11W S14 Lamps
- Long Life: 50,000 Hours
- Application Friendly: UV Free & IR Free
- Environmentally Friendly: Mercury Free, Lead Free and RoHS Compliant
- 5-Year Limited Warranty

APPLICATIONS

- Signs
- Marquees
- Amusement Lighting
- Accent Lighting
- Indoor and Outdoor

SPECIFICATIONS



**S14
E26 Base**

Watts (W)	Ordering Code	Lamp Description	Bulb Type	Volts (V)	Color	Lumens (lm)	Average Rated Life (h)	Case Qty
2	1003931	UTOPIA LED S14, RED	S14	120	Red	N/A	50000	16
2	1003932	UTOPIA LED S14. GREEN	S14	120	Green	N/A	50000	16
2	1003933	UTOPIA LED S14, BLUE	S14	120	Blue	N/A	50000	16
2	1003934	UTOPIA LED S14, YELLOW	S14	120	Yellow	N/A	50000	16

CAUTION:

This lamp may not be compatible with all dimmers. Check www.ushio.com to find up to date dimmer compatibility options. Use only 120V 60Hz circuits. Do not open. No user serviceable parts inside. This device is not intended for use with emergency exit fixtures, emergency exit lights, photo controls or electric timers. Fully enclosed or recessed fixtures must contain proper ventilation. Reliable Operating temperature is -4°F to 113°F. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.